



116 Rye




216 Hemp




170 Elmwood



256 Millet




173 Nutshell



559 Frosted Oats




174 Fir




564 Freekeh




174 Fir




568 Flaxseed




572 Milo



684 Farro




740 Barley



769 Amaranth




774 Wheat



775 Spelt




5012 English Grey




5013 Drift




5016 Ember




5019 Briarwood




7003 Sandalwood



7004 Cotton Seed



7007 Oakwood



7008 Burlwood

Style Name	In The Grain II 20 mil
Style Number	5525V
Construction	High Performance Luxury Vinyl Tile
Class / ASTM F1700	Class III Printed Film Vinyl Tile, Type B (embossed)
Finish	ExoGuard+ [®]

	U.S.	Metric
Nominal Dimensions	6 in w, 48 in l	15 cm w, 122 cm l
Actual Dimensions	5.96 in w, 48 in l	15.14 cm w, 121.92 cm l
Wear Layer Thickness	20 mil (0.02 in)	0.51 mm
Overall Thickness	0.098 in	2.5 mm
Installation	Direct Glue	
Recommended / Required Adhesive	Shaw 4100 or S150	

Packaging


Pieces per box	21 pcs	
Area per box	41.72 sq ft	3.88 sq m
Weight per box	35.44 lbs	16.08 kg




Recommended Installation Method



Ashlar



Brick



Herringbone



Monolithic



Stagger

Performance Testing

Static Load (ASTM F970)	Passes (Modified), *1500 lbs
Residual Indentation (ASTM F1914)	Passes
Resistance to Heat (ASTM F1514)	Passes
Resistance to Light (ASTM F1515)	Passes
Resistance to Chemicals (ASTM F925)	Passes
Radiant Panel (ASTM E648)	Passes, Class I
Slip Resistance (ASTM D2047)	ADA compliant

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

Commercial Limited Underbed Bond Warranty S150/4151/LokWorx+ Resilient
Resilient 15 Year Commercial Limited

Environmental

Indoor Air Quality	FloorScore [®] Certified
Recycled Content	Pre-consumer - 30%, Post-consumer - 0%



made in USA

Specifications are subject to nominal manufacturing variance.
Material supply and/or manufacturing processes may necessitate changes without notice.